



## 1-stage add-on (no-frame) glycol-chiller/HX

These specifications were provided through Thermaline's sizing calculators on February 18th, 2026.

<b>Unit part number:</b>	16000-GL13-11	
<b>Unit description:</b>	T13 Glycol trim cooling section with 11 plates and center frame	
<b>Model</b>	T13	
<b>Number of plates</b>	11	
<b>Maximum BTU load</b>	140000	
	<b>Beer-wort</b>	<b>Glycol</b>
<b>Initial temperature</b>	70°F	
<b>Final temperature</b>	50°F	
<b>Flow rate</b>	20 GPM (max.)	40 GPM (min.)

**Please contact Thermaline for drawing of unit**

Tighten inside dimensions between 1-11/16" (minimum) and 1-3/4" (maximum)

**CAUTION- DO NOT TIGHTEN BELOW MINIMUM DIMENSION**

Plates are constructed of 304SS unless specified otherwise.

Prices quoted do not include freight or shipping. Any Federal, State, or Local Taxes and Import, Export or Foreign Duties are the responsibility of the Buyer. We reserve the right to add a service charge to overdue accounts. [Thermaline Terms & Conditions](#).

 Proudly manufactured in the U.S.A. by Thermaline • Auburn, WA • [Thermaline.com](#) 